Page 1/11

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 30.07.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: H089 2K RMC SPECIAL HARDENER
- · Article number: H089
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** use as industrial paint
- · Sector of Use

SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category

PC9a Coatings and paints, thinners, paint removers
 PC9b Fillers, putties, plasters, modelling clay
 Application of the substance / the mixture refer to the relevant Technical Data Sheet

- \cdot 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: P.O. Box 7623 Beirut LEBANON info@generalpaint.biz Générale de Peinture, 70 Rue Cortambert 75116 Paris, France Tel:+33(0)175293559
- · Further information obtainable from: Product Safety Department
- · 1.4 Emergency telephone number: +33 (0)6 07 87 13 41

SECTION 2: Hazards identification

 2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008) with its amendment Regulation (EU) 2020/878



Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Irrit. 2H315 Causes skin irritation.Eye Irrit. 2H319 Causes serious eye irritation.STOT SE 3H335 May cause respiratory irritation.

(Contd. on page 2)



Page 2/11

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 30.07.2024



	(Contd. of page 1
2.2 Label el	ements
Labelling ad	ccording to Regulation (EC) No 1272/2008
	is classified and labelled according to the GB CLP regulation.
Hazard pict	ograms
~	∧
Jul /	
<u> 27</u>	
GHS02 G	HS07
Signal word	I Warning
Hazard-dete	ermining components of labelling:
	er of hexamethylene diisocyanate
Hazard stat	
H226 Flamn	nable liquid and vapour.
	es skin irritation.
H319 Cause	es serious eye irritation.
	ause respiratory irritation.
	ary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources
	No smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P303+P361-	+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse ski
	with water [or shower].
P305+P351	+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contac lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/nationa international regulations.
Additional i	information:
	xamethylene-di-isocyanate. May produce an allergic reaction.
2.3 Other ha	
	PBT and vPvB assessment
PBT: Not ap	
vPvB: Not ap	
vrvd. NOLA	ppiloane.

GB (Contd. on page 3)

Page 3/11

Safety data sheet

according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 30.07.2024

Trade name: H089 2K RMC SPECIAL HARDENER

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 28182-81-2 Reg.nr.: 01-2119485796-17	Homopolymer of hexamethylene diisocyanate ♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	>25- <i>≤</i> 50%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	2-butoxyethyl acetate Acute Tox. 4, H312; Acute Tox. 4, H332	>25- <i>≤</i> 50%
CAS: 763-69-9 EINECS: 212-112-9	ethyl 3-ethoxypropionate Flam. Liq. 3, H226; Skin Irrit. 2, H315; Eye Irrit. 2, H319	>10- <i>≤</i> 25%
CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119455851-35 05-2116598517-27	Solvent naphtha (petroleum), light arom. 〈〉 Acute Tox. 4, H332; STOT SE 3, H335	>10- <i>≤</i> 25%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate 🔗 Flam. Liq. 3, H226; 🐠 STOT SE 3, H336	>10- <i>≤</i> 25%
· Additional information: Fo	r the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

---- GB

(Contd. on page 4)

Page 4/11

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 30.07.2024

Trade name: H089 2K RMC SPECIAL HARDENER

(Contd. of page 3)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3

(Contd. on page 5)

GB

Page 5/11

Safety data sheet

according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 30.07.2024

Trade name: H089 2K RMC SPECIAL HARDENER

· 7.3 Specific end use(s) No further relevant information available.

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see section 7.

· Ingredients with limit values that require monitoring at the workplace:

112-07-2 2-butoxyethyl acetate

WEL Short-term value: 332 mg/m³, 50 ppm Long-term value: 133 mg/m³, 20 ppm Sk

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

⁻ GB

Page 6/11

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 30.07.2024

(Contd. of page 5)

Trade name: H089 2K RMC SPECIAL HARDENER

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and o General Information	
Appearance:	
Form:	Liquid
Colour:	Clear
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: 124 °C
Flash point:	25 ℃
Flammability (solid, gas):	Flammable.
Auto-ignition temperature:	280 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	0.7 Vol %
Upper:	8.4 Vol %
Vapour pressure at 20 °C:	10.7 hPa
Density at 20 °C:	1.037 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.

- GB

Page 7/11

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 30.07.2024

Trade name: H089 2K RMC SPECIAL HARDENER

	(Contd. of pag
· Evaporation rate	Not determined.
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
 Viscosity: Dynamic: Kinematic: 	Not determined. Not determined.
 Solvent content: Organic solvents: VOC (EC) 	62.9 % 652.7 g/l
Solids content:	62.8 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.

(Contd. on page 8)

GB

Page 8/11

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 30.07.2024

(Contd. of page 7)

Trade name: H089 2K RMC SPECIAL HARDENER

- **Reproductive toxicity** Based on available data, the classification criteria are not met. • **STOT-single exposure**
- May cause respiratory irritation.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information • 14.1 UN-Number • ADR, IMDG, IATA UN1263 • 14.2 UN proper shipping name • ADR 1263 PAINT • IMDG, IATA PAINT

Page 9/11

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 30.07.2024

Trade name: H089 2K RMC SPECIAL HARDENER

····	(Contd. of page 8
14.3 Transport hazard class(es)	NOT APPLICABLE
· ADR, IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	III
14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
· EMS Number: · Stowage Category	F-E, <u>S-E</u> A
· 14.7 Transport in bulk according to Annex II o	
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	5L
 Limited quantities (LQ) Excepted quantities (EQ) 	SL Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 m
· Transport category	3 D/F
· Tunnel restriction code	D/E
· IMDG	51
 Limited quantities (LQ) Excepted quantities (EQ) 	SL Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 m
· UN "Model Regulation":	UN 1263 PAINT, 3, III

(Contd. on page 10)

Page 10/11

Safety data sheet

according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 30.07.2024

Trade name: H089 2K RMC SPECIAL HARDENER

(Contd. of page 9)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

- H312 Harmful in contact with skin.
- H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Product safety department
- · Contact: N/A

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 11)

Page 11/11

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 30.07.2024

Trade name: H089 2K RMC SPECIAL HARDENER

IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 • * Data compared to the previous version altered.	(Contd. of page 10)
--	---------------------