

Page 1/11


Safety data sheet

according to UK REACH

Printing date 06.08.2024

Version number 1.2

Revision: 06.08.2024





Page 2/11

Safety data sheet

according to UK REACH Version number 1.2

Revision: 06.08.2024

Trade name: B002 BASECOAT METALLIC ADDITIVE

Printing date 06.08.2024

2.2 Label el	(Contd. of page
	ccording to Regulation (EC) No 1272/2008
	t is classified and labelled according to the GB CLP regulation.
Hazard pict	
	ograms
	\wedge
< **>><	
GHS02 G	HS07
0	
Signal word	1 Warning
Hazard-det	ermining components of labelling:
n-butyl aceta	
Hazard stat	ements
	nable liquid and vapour.
	es skin irritation.
H336 May c	ause drowsiness or dizziness.
	ary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition source. No smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361	+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse ski with water [or shower].
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/nationa international regulations.
2.3 Other h	•
Results of I	PBT and vPvB assessment

SECTION 3: Composition/information on ingredients • 3.2 Chemical characterisation: Mixtures • Description: Mixture of substances listed below with nonhazardous additions. • Dangerous components: CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29 • Flam. Liq. 3, H226; • STOT SE 3, H336 (Contd. on page 3)

Page 3/11

Safety data sheet according to UK REACH

Printing date 06.08.2024

Version number 1.2

Revision: 06.08.2024

Trade name: B002 BASECOAT METALLIC ADDITIVE

CAS: 64742-95-6 Solvent naphtha (petroleum), light arom. >2.5-≤10% EINECS: 265-199-0 Acute Tox. 4, H332; STOT SE 3, H335 >2.5-≤10% Reg.nr.: 01-2119455851-35 Acute Tox. 4, H332; STOT SE 3, H335 >2.5-≤10% CAS: 108-65-6 2-methoxy-1-methylethyl acetate ≤2.5% EINECS: 203-603-9 Flam. Liq. 3, H226 <2.5% 05-2116413226-56 <2.5%	1 L	xylene	contd. of page 2) >25-≤50%
EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	EINECS: 265-199-0 Reg.nr.: 01-2119455851-35		>2.5- <i>≤</i> 10%
	EINECS: 203-603-9 Reg.nr.: 01-2119475791-29		<i>≤</i> 2.5%

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- \cdot 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

(Contd. on page 4)

GB

Page 4/11

Safety data sheet

according to UK REACH

Printing date 06.08.2024

Version number 1.2

Revision: 06.08.2024

Trade name: B002 BASECOAT METALLIC ADDITIVE

(Contd. of page 3)

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Additional information about design of technical facilities: No further data; see section 7.

· Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

(Contd. on page 5)

GB ·

Page 5/11

Safety data sheet according to UK REACH

Printing date 06.08.2024

Version number 1.2

Revision: 06.08.2024

(Contd. on page 6)

GB

Trade name: B002 BASECOAT METALLIC ADDITIVE

((Contd. of page 4
	-20-7 xylene
WEL	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV
108-6	5-6 2-methoxy-1-methylethyl acetate
	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk
Inare	dients with biological limit values:
-	-20-7 xylene
BMG	V 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
Addi	tional information: The lists valid during the making were used as basis.
Avoic Resp In ca expos	l contact with the skin. I contact with the eyes and skin. iratory protection: se of brief exposure or low pollution use respiratory filter device. In case of intensive or longe sure use self-contained respiratory protective device. Action of hands:
Mass Lu	Protective gloves
Due prepa Selec degra	nove material has to be impermeable and resistant to the product/ the substance/ the preparation to missing tests no recommendation to the glove material can be given for the product/ the mation/ the chemical mixture. Stion of the glove material on consideration of the penetration times, rates of diffusion and the mation rial of gloves
The s quali	election of the suitable gloves does not only depend on the material, but also on further marks o
	ty and varies from manufacturer to manufacturer. As the product is a preparation of sever ances, the resistance of the glove material can not be calculated in advance and has therefore ecked prior to the application.



Page 6/11

Safety data sheet

according to UK REACH

Printing date 06.08.2024

Version number 1.2

Revision: 06.08.2024

(Contd. of page 5)

Trade name: B002 BASECOAT METALLIC ADDITIVE

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

 9.1 Information on basic physical and c General Information 	nemical properties
· Appearance:	
Form:	Liquid
Colour:	Colourless
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	124 °C
· Flash point:	27 °C
· Flammability (solid, gas):	Flammable.
· Auto-ignition temperature:	370 °C
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
· Vapour pressure at 20 °C:	10.7 hPa
· Density at 20 °C:	0.962 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

- GB

Page 7/11

Safety data sheet according to UK REACH

Printing date 06.08.2024

Version number 1.2

Revision: 06.08.2024

Trade name: B002 BASECOAT METALLIC ADDITIVE

	(Contd. of page
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	76.0 %
VÕC (EC)	731.3 g/l
Solids content:	24.0 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

- · Primary irritant effect:
- Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

(Contd. on page 8)



Page 8/11

Safety data sheet

according to UK REACH

Printing date 06.08.2024

Version number 1.2

Revision: 06.08.2024

(Contd. of page 7)

Trade name: B002 BASECOAT METALLIC ADDITIVE

· Additional toxicological information:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR, IMDG, IATA

UN1263

(Contd. on page 9)

GB

Page 9/11

Safety data sheet according to UK REACH

Printing date 06.08.2024

Version number 1.2

Revision: 06.08.2024

Trade name: B002 BASECOAT METALLIC ADDITIVE

14.2 UN proper shipping name	(Contd. of page 8
ADR MDG, IATA	1263 PAINT PAINT
14.3 Transport hazard class(es)	NOT APPLICABLE
ADR, IMDG, IATA	
• Class • Label	3 Flammable liquids. 3
• 14.4 Packing group • ADR, IMDG, IATA	<i>III</i>
• 14.5 Environmental hazards: • Marine pollutant:	No
• 14.6 Special precautions for user • EMS Number: • Stowage Category	Warning: Flammable liquids. F-E, <u>S-E</u> A
14.7 Transport in bulk according to An Marpol and the IBC Code	nex II of Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m
UN "Model Regulation":	UN 1263 PAINT, 3, III

(Contd. on page 10)

Page 10/11

Safety data sheet

according to UK REACH

Printing date 06.08.2024

Version number 1.2

Revision: 06.08.2024

Trade name: B002 BASECOAT METALLIC ADDITIVE

(Contd. of page 9)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 11)

GB



Safety data sheet according to UK REACH

Printing date 06.08.2024

Version number 1.2

Revision: 06.08.2024

Page 11/11

Trade name: B002 BASECOAT METALLIC ADDITIVE

	(Contd. of page 10)
EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Liq. 3: Flammable liquids – Category 3	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
 * Data compared to the previous version altered. 	
	GB —