

Page 1/11


# Safety data sheet

according to UK REACH

Printing date 05.08.2024

Version number 1.1

Revision: 05.08.2024





Page 2/11

# Safety data sheet according to UK REACH

Printing date 05.08.2024

Version number 1.1

Revision: 05.08.2024

# Trade name: B010 BASECOAT CONCENTRATED WHITE

· Hazard pict	(Contd. of page
nazaru pici	ogranis
	$\wedge$
<b>&lt; {}</b>	
	$\checkmark$
GHS02 GI	HS07
· Signal word	I Warning
· Hazard-dete	ermining components of labelling:
n-butyl aceta	
· Hazard stat	ements
H226 Flamm	nable liquid and vapour.
	ause drowsiness or dizziness.
	ary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition source
	No smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361-	+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse sk
	with water [or shower].
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national international regulations.
2.3 Other ha	
Results of F	PBT and vPvB assessment
· PBT: Not ap	plicable.

· vPvB: Not applicable.

# SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

GB



### Page 3/11

# Safety data sheet

according to UK REACH

Printing date 05.08.2024

Version number 1.1

Revision: 05.08.2024

### Trade name: B010 BASECOAT CONCENTRATED WHITE

CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate � Flam. Liq. 3, H226; 🐠 STOT SE 3, H336	>25- <i>≤</i> 50%
	xylene	>2.5- <i>≤</i> 10%
CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119455851-35 05-2116598517-27	Solvent naphtha (petroleum), light arom. � Acute Tox. 4, H332; STOT SE 3, H335	>2.5- <i>≤</i> 10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29 05-2116413226-56	2-methoxy-1-methylethyl acetate	>2.5- <i>≤</i> 10%

# SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

# SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)

GB



#### Page 4/11

# Safety data sheet

according to UK REACH

Printing date 05.08.2024

Version number 1.1

Revision: 05.08.2024

### Trade name: B010 BASECOAT CONCENTRATED WHITE

#### · 5.3 Advice for firefighters

· Protective equipment: No special measures required.

(Contd. of page 3)

#### SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- **6.3** Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
   See Section 13 for disposal information.

# SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
   Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see section 7.

(Contd. on page 5)



### Page 5/11

# Safety data sheet

according to UK REACH

Printing date 05.08.2024

Version number 1.1

Revision: 05.08.2024

# Trade name: B010 BASECOAT CONCENTRATED WHITE

	(Contd. of page 4)
-	lients with limit values that require monitoring at the workplace:
123-86	6-4 n-butyl acetate
WEL S	Short-term value: 966 mg/m³, 200 ppm
1	Long-term value: 724 mg/m³, 150 ppm
1330-2	20-7 xylene
WEL S	Short-term value: 441 mg/m³, 100 ppm
	Long-term value: 220 mg/m <sup>3</sup> , 50 ppm
3	Sk; BMGV
108-65	5-6 2-methoxy-1-methylethyl acetate
WEL S	Short-term value: 548 mg/m³, 100 ppm
1	Long-term value: 274 mg/m³, 50 ppm
3	Sk
Ingred	lients with biological limit values:
1330-2	20-7 xylene
BMGV	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid
Additi	onal information: The lists valid during the making were used as basis.
8.2 Fx	posure controls
	nal protective equipment:
	al protective and hygienic measures:
Immea	liately remove all soiled and contaminated clothing
	hands before breaks and at the end of work.
Respir	ratory protection:
In case	e of brief exposure or low pollution use respiratory filter device. In case of intensive or longe ure use self-contained respiratory protective device.
_	

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

<sup>-</sup> GB



# Page 6/11

# Safety data sheet

according to UK REACH

Printing date 05.08.2024

Version number 1.1

Revision: 05.08.2024

(Contd. of page 5)

# Trade name: B010 BASECOAT CONCENTRATED WHITE

### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Phy	vsical and chem	ical properties	

General Information Appearance:	
Form:	Liquid
Colour:	White
· Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	e: 120 °C
Flash point:	27 °C
· Flammability (solid, gas):	Flammable.
Auto-ignition temperature:	370 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosiv air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
Vapour pressure at 20 °C:	10.7 hPa
· Density at 20 °C:	1.26 g/cm³
Relative density	Not determined.
Vapour density	Not determined.

## Page 7/11

# Safety data sheet according to UK REACH

Printing date 05.08.2024

Version number 1.1

Revision: 05.08.2024

### Trade name: B010 BASECOAT CONCENTRATED WHITE

	(Contd. of page
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	45.1 %
VÕC (EC)	567.7 g/l
Solids content:	55.0 %
9.2 Other information	No further relevant information available.

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

# · LD/LC50 values relevant for classification:

Oral	<b>n-butyl ac</b> LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)
Primary i	rritant effe	ct:

• Serious eye damage/irritation Based on available data, the classification criteria are not met.

• **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

(Contd. on page 8)

GB



### Page 8/11

# Safety data sheet

according to UK REACH

Printing date 05.08.2024

Version number 1.1

Revision: 05.08.2024

(Contd. of page 7)

### Trade name: B010 BASECOAT CONCENTRATED WHITE

· Additional toxicological information:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

• Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

# **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

· 12.2 Persistence and degradability No further relevant information available.

• 12.3 Bioaccumulative potential No further relevant information available.

• 12.4 Mobility in soil No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

· 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

• **12.6 Other adverse effects** No further relevant information available.

# SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

# SECTION 14: Transport information

· 14.1 UN-Number

· ADR, IMDG, IATA

UN1263

(Contd. on page 9)

GB



## Page 9/11

# Safety data sheet according to UK REACH

Printing date 05.08.2024

Version number 1.1

Revision: 05.08.2024

# Trade name: B010 BASECOAT CONCENTRATED WHITE

	(Contd. of page
· 14.2 UN proper shipping name · ADR · IMDG, IATA	1263 PAINT PAINT
· 14.3 Transport hazard class(es)	NOT APPLICABLE
· ADR, IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· IMDG, IATA	III
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Stowage Category	A
· 14.7 Transport in bulk according to Ann	ex II of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
·IMDG	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 r
· UN "Model Regulation":	UN 1263 PAINT, 3

# SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

# · Regulated explosives precursors

None of the ingredients is listed.

(Contd. on page 10)

GB



### Page 10/11

# Safety data sheet

according to UK REACH

Printing date 05.08.2024

Version number 1.1

Revision: 05.08.2024

### Trade name: B010 BASECOAT CONCENTRATED WHITE

(Contd. of page 9)

# · Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

## Reportable poisons

None of the ingredients is listed.

#### · Directive 2012/18/EU

- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

#### · Department issuing SDS: Product safety department

#### · Contact: N/A

### • Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2

(Contd. on page 11)

GB



# Safety data sheet according to UK REACH

Printing date 05.08.2024

Version number 1.1

Revision: 05.08.2024

Trade name: B010 BASECOAT CONCENTRATED WHITE

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 · \* **Data compared to the previous version altered.** 

(Contd. of page 10)

Page 11/11

GB -