

Page 1/11


Safety data sheet

according to UK REACH

Printing date 05.08.2024

Version number 1.1

Revision: 05.08.2024





Page 2/11

Safety data sheet according to UK REACH

Printing date 05.08.2024

Version number 1.1

Revision: 05.08.2024

Trade name: B150 BASECOAT RADIANT BLUE

	(Contd. of page 1)
2.2 Label el	ements
Labelling ad	ccording to Regulation (EC) No 1272/2008
The product	is classified and labelled according to the GB CLP regulation.
Hazard pict	
<u> </u>	A
<u> < 🕲 > (</u>	
	\checkmark
GHS02 GI	H\$07
Signal word	I Warning
	ermining components of labelling:
n-butyl aceta	ate
Hazard state	ements
	nable liquid and vapour.
H315 Cause	s skin irritation.
H336 May ca	ause drowsiness or dizziness.
Precautiona	ary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
	No smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361-	+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin
D405	with water [or shower].
P405 P501	Store locked up.
F301	Dispose of contents/container in accordance with local/regional/national/
22 Othor b	international regulations.
2.3 Other ha	
	PBT and vPvB assessment
PBT: Not ap	
vPvB: Not a	ppilcable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

 Dangerous components: 			
CAS: 123-86-4	n-butyl acetate	>25- <i>≤</i> 50%	
EINECS: 204-658-1	🚸 Flam. Lig. 3, H226; 🚸 STOT SE 3, H336		
Reg.nr.: 01-2119485493-29			
L	(C	ontd. on page 3)	
		GB	3 —



Page 3/11

Safety data sheet according to UK REACH

Printing date 05.08.2024

Version number 1.1

Revision: 05.08.2024

Trade name: B150 BASECOAT RADIANT BLUE

CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119486136-34 05-2116602925-45 01-2119488216-32	xylene ♦ Flam. Lig. 3, H226; ♦ Acute Tox. 4, H312; Acute Tox. 4,	Contd. of page 2) >10- <i>≤</i> 25%
CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119455851-35 05-2116598517-27	Solvent naphtha (petroleum), light arom. � Acute Tox. 4, H332; STOT SE 3, H335	>2.5- <i>≤</i> 10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29 05-2116413226-56	2-methoxy-1-methylethyl acetate 🔗 Flam. Liq. 3, H226	>2.5- <i>≤</i> 10%
CAS: 123-42-2 EINECS: 204-626-7 • Additional information: For	diacetone alcohol, technical	<i>≤</i> 2.5%

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.

(Contd. on page 4)

GB



Page 4/11

Safety data sheet

according to UK REACH

Printing date 05.08.2024

Version number 1.1

Revision: 05.08.2024

Trade name: B150 BASECOAT RADIANT BLUE

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

(Contd. of page 3)

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- **6.3** Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Additional information about design of technical facilities: No further data; see section 7.

(Contd. on page 5)



Page 5/11

Safety data sheet according to UK REACH

Printing date 05.08.2024

Version number 1.1

Revision: 05.08.2024

Trade name: B150 BASECOAT RADIANT BLUE

. Inara	(Contd. of page dients with limit values that require monitoring at the workplace:
-	36-4 n-butyl acetate
	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm
1330	20-7 xylene
	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV
108-6	5-6 2-methoxy-1-methylethyl acetate
WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
123-4	2-2 diacetone alcohol, technical
WEL	Short-term value: 362 mg/m³, 75 ppm Long-term value: 241 mg/m³, 50 ppm
· Ingre	dients with biological limit values:
1330	-20-7 xylene
Divio	V 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
· Addi	tional information: The lists valid during the making were used as basis.
 Perse Gene Keep Imme Wash Avoid Avoid Resp In case exposition 	xposure controls onal protective equipment: eral protective and hygienic measures: away from foodstuffs, beverages and feed. adiately remove all soiled and contaminated clothing a hands before breaks and at the end of work. I contact with the skin. I contact with the eyes and skin. iratory protection: se of brief exposure or low pollution use respiratory filter device. In case of intensive or long sure use self-contained respiratory protective device.
Max. UL	Protective gloves
The g	love material has to be impermeable and resistant to the product/ the substance/ the preparatio



Page 6/11

Safety data sheet

according to UK REACH

Printing date 05.08.2024

Version number 1.1

Revision: 05.08.2024

Trade name: B150 BASECOAT RADIANT BLUE

(Contd. of page 5)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection:



Tightly sealed goggles

9.1 Information on basic physical a	and chemical properties	
General Information Appearance:		
Form:	Liquid	
Colour:	Blue	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling ra	ange: 120 °C	
Flash point:	27 °C	
Flammability (solid, gas):	Flammable.	
Auto-ignition temperature:	370 °C	
Decomposition temperature:	Not determined.	
Ignition temperature:	Product is not selfigniting.	

Page 7/11

Safety data sheet according to UK REACH

Printing date 05.08.2024

Version number 1.1

Revision: 05.08.2024

Trade name: B150 BASECOAT RADIANT BLUE

	(Contd. of page 6
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
· Vapour pressure at 20 °C:	10.7 hPa
· Density at 20 °C:	0.966 g/cm³
Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	74.7 %
VÕC (EC)	721.8 g/l
Solids content:	25.3 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.3 Possibility of nazardous reactions no dangerous reactions know
- **10.4 Conditions to avoid** No number relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

(Contd. on page 8)

GB

Page 8/11

Safety data sheet

according to UK REACH

Printing date 05.08.2024

Version number 1.1

Revision: 05.08.2024

Trade name: B150 BASECOAT RADIANT BLUE

(Contd. of page 7)

SECTION	11. Tovia	alagiaal	information
SECTION	II. IOXI	cological	information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
	1050/11	

Inhalative LC50/4 h >21 mg/l (rat)

· Primary irritant effect:

· Skin corrosion/irritation

- Causes skin irritation.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 9)

GB



Page 9/11

Safety data sheet

according to UK REACH

Printing date 05.08.2024

Version number 1.1

Revision: 05.08.2024

Trade name: B150 BASECOAT RADIANT BLUE

· 12.6 Other adverse effects No further relevant information available.

(Contd. of page 8)

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
 Recommendation
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

OFOTION			
SECULAN	11. Iran	enort intorr	nation
	14.161	sport inforr	

14.1 UN-Number ADR, IMDG, IATA	UN1263	
<i>14.2 UN proper shipping name ADR IMDG, IATA</i>	1263 PAINT PAINT	
14.3 Transport hazard class(es)	NOT APPLICABLE	
ADR, IMDG, IATA		
Class Label	3 Flammable liquids.	
	3	
14.4 Packing group ADR, IMDG, IATA	<i>III</i>	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Warning: Flammable liquids.	
EMS Number:	F-E, <u>S-Ē</u>	
Stowage Category	A	
14.7 Transport in bulk according to Anne Marpol and the IBC Code	ex II of Not applicable.	
-		(Contd. on page



Page 10/11

Safety data sheet

according to UK REACH

Printing date 05.08.2024

Version number 1.1

Revision: 05.08.2024

Trade name: B150 BASECOAT RADIANT BLUE

	(Contd. of page 9)
· Transport/Additional information:	
 ADR Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
 Transport category Tunnel restriction code 	3 D/E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 11)



Page 11/11

Safety data sheet according to UK REACH

Printing date 05.08.2024

Version number 1.1

Revision: 05.08.2024

Trade name: B150 BASECOAT RADIANT BLUE

(Contd. of page 10)

This information is based on our present knowledge any specific product features and shall not establish Relevant phrases H226 Flammable liquid and vapour. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.	a legally valid contractual relationship.
 H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. 	
 H226 Flammable liquid and vapour. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. 	
 H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. 	
H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation.	
H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation.	
H332 Harmful if inhaled. H335 May cause respiratory irritation.	
H335 May cause respiratory irritation.	
m330 way cause drowsiness or dizziness.	
Department issuing SDS: Product safety departme	ent
Contact: N/A	
Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchai	ndises dangereuses par chemin de fer (Regulations Concern
the International Transport of Dangerous Goods by Rail)	
ICAO: International Civil Aviation Organisation	
ADR: Accord relatif au transport international des marchandises	angereuses par route (European Agreement Concerning
International Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling	a of Chemicals
EINECS: European Inventory of Existing Commercial Chemical St	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chem	nical Society)
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Liq. 3: Flammable liquids – Category 3	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	00001/2
STOT SE 3: Specific target organ toxicity (single exposure) – Cate * Data compared to the previous version altered.	egory 3