


Page 1/11

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 06.08.2024





Page 2/11

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 06.08.2024

Trade name: B370 BASECOAT ORANGE

	(Contd. of page 1)
2.2 Label el	ements
Labelling ad	ccording to Regulation (EC) No 1272/2008
	is classified and labelled according to the GB CLP regulation.
Hazard pict	
< 😗 > (
	\checkmark
GHS02 GI	HS07
Signal word	l Warning
	ermining components of labelling:
n-butyl aceta	
Hazard stat	
	nable liquid and vapour.
	s skin irritation.
H336 May ca	ause drowsiness or dizziness.
	ary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361-	P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/
	international regulations.
2.3 Other ha	
Results of F	PBT and vPvB assessment
PBT: Not ap	
vPvB: Not a	

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

l	 Dangerous components: 		
ſ	CAS: 123-86-4	n-butyl acetate	>25- <i>≤</i> 50%
l	EINECS: 204-658-1	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	1
l	Reg.nr.: 01-2119485493-29		
		(C	Contd. on page 3)



Page 3/11

Safety data sheet according to UK REACH

according to

Printing date 07.08.2024

Version number 1.1

Revision: 06.08.2024

Trade name: B370 BASECOAT ORANGE

	xylene 🚸 Flam. Lig. 3, H226; 🚸 Acute Tox. 4, H312; Acute Tox. 4,	Contd. of page 2) >10-≤25%
	Solvent naphtha (petroleum), light arom. ① Acute Tox. 4, H332; STOT SE 3, H335	>2.5- <i>≤</i> 10%
	2-methoxy-1-methylethyl acetate 🔗 Flam. Liq. 3, H226	<i>≤</i> 2.5%
EINECS: 203-905-0 Reg.nr.: 01-2119475108-36	2-butoxyethanol Acute Tox. 3, H311; Acute Tox. 3, H331; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	<i>≤</i> 2.5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

(Contd. on page 4)

GB



Page 4/11

Safety data sheet according to UK REACH

according to UK RE

Printing date 07.08.2024

Version number 1.1

Revision: 06.08.2024

Trade name: B370 BASECOAT ORANGE

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

(Contd. of page 3)

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- **6.3** Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see section 7.

(Contd. on page 5)



Page 5/11

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 06.08.2024

Trade name: B370 BASECOAT ORANGE

	(Contd. of page
	dients with limit values that require monitoring at the workplace:
	6-4 n-butyl acetate
WEL	Short-term value: 966 mg/m ³ , 200 ppm
	Long-term value: 724 mg/m³, 150 ppm
	20-7 xylene
WEL	Short-term value: 441 mg/m ³ , 100 ppm
	Long-term value: 220 mg/m ³ , 50 ppm
	Sk; BMGV
	5-6 2-methoxy-1-methylethyl acetate
WEL	Short-term value: 548 mg/m³, 100 ppm
	Long-term value: 274 mg/m³, 50 ppm
	Sk
	6-2 2-butoxyethanol
WEL	Short-term value: 246 mg/m³, 50 ppm
	Long-term value: 123 mg/m³, 25 ppm
	Sk, BMGV
Ingre	dients with biological limit values:
1330-	20-7 xylene
BMG	/ 650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid
	6-2 2-butoxyethanol
BMG	/ 240 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: butoxyacetic acid
Addit	ional information: The lists valid during the making were used as basis.
8.2 Ex	cposure controls
	, onal protective equipment:
	ral protective and hygienic measures:
	away from foodstuffs, beverages and feed.
	diately remove all soiled and contaminated clothing
Wash	hands before breaks and at the end of work.
	contact with the skin.
	contact with the eyes and skin.
	iratory protection:
	e of brief exposure or low pollution use respiratory filter device. In case of intensive or lor
expos	ure use self-contained respiratory protective device.
	(Contd. on page



Page 6/11

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 06.08.2024

(Contd. of page 5)

Trade name: B370 BASECOAT ORANGE

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

 9.1 Information on basic physical General Information 	and chemical properties	
Appearance:		
Form:	Liquid	
Colour:	Orange	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
pH-value:	Not determined.	
· Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling	range: 120 °C	
Flash point:	27 °C	
· Flammability (solid, gas):	Flammable.	

Page 7/11

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 06.08.2024

Trade name: B370 BASECOAT ORANGE

	(Contd. of page 6)
· Auto-ignition temperature:	370 °C
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
· Vapour pressure at 20 °C:	10.7 hPa
· Density at 20 °C:	0.946 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	76.8 %
VÕC (EC)	726.8 g/l
Solids content:	23.1 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 8)

GB

Page 8/11

Safety data sheet

according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 06.08.2024

Trade name: B370 BASECOAT ORANGE

(Contd. of page 7)

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

- Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 9)

Page 9/11

Safety data sheet

according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 06.08.2024

Trade name: B370 BASECOAT ORANGE

· 12.6 Other adverse effects No further relevant information available.

(Contd. of page 8)

SECTION 13: Disposal considerations

13.1 Waste treatment methods
 Recommendation
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information · 14.1 UN-Number · ADR, IMDG, IATA UN1263 · 14.2 UN proper shipping name · ADR 1263 PAINT · IMDG, IATA PAINT · 14.3 Transport hazard class(es) NOT APPLICABLE · ADR, IMDG, IATA · Class 3 Flammable liquids. · Label 3 · 14.4 Packing group · ADR, IMDG, IATA $\parallel \parallel$ · 14.5 Environmental hazards: · Marine pollutant: No Warning: Flammable liquids. · 14.6 Special precautions for user · EMS Number: F-E,S-E · Stowage Category Α · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. (Contd. on page 10) GB



Page 10/11

Safety data sheet

according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 06.08.2024

Trade name: B370 BASECOAT ORANGE

	(Contd. of page 9)
· Transport/Additional information:	
 ADR Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
 Transport category Tunnel restriction code 	3 D/E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 11)



Page 11/11

Safety data sheet according to UK REACH

Printing date 07.08.2024

Version number 1.1

Revision: 06.08.2024

Trade name: B370 BASECOAT ORANGE

(Contd. of page 10)

GB

	1 16: Other information
	ation is based on our present knowledge. However, this shall not constitute a guarantee product features and shall not establish a legally valid contractual relationship.
Relevant p	
	nable liquid and vapour.
	ful if swallowed.
	in contact with skin.
	ful in contact with skin.
	es skin irritation.
	es serious eye irritation.
H331 Toxic	ir innaied. ful if inhaled.
	ause respiratory irritation.
	ause drowsiness or dizziness.
	t issuing SDS: Product safety department
Contact: N	
Abbreviati	ons and acronyms: A international concernant la transport des marchandises denservuese per chemin de fer (Desulations Concern
the Internation	nt international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concern al Transport of Dangerous Goods by Rail)
ICAO: Internat	ional Civil Aviation Organisation
	elatif au transport international des marchandises dangereuses par route (European Agreement Concerning
	arriage of Dangerous Goods by Road) ional Maritime Code for Dangerous Goods
	onal Air Transport Association
	Harmonised System of Classification and Labelling of Chemicals
	pean Inventory of Existing Commercial Chemical Substances pean List of Notified Chemical Substances
	I Abstracts Service (division of the American Chemical Society)
VOC: Volatile	Organic Compounds (USA, EU)
	oncentration, 50 percent ose, 50 percent
	it. Bioaccumulative and Toxic
vPvB: very Pe	sistent and very Bioaccumulative
	lammable liquids – Category 3
	Acute toxicity – Category 3 Acute toxicity – Category 4
Skin Irrit. 2: Sk	in corrosion/irritation – Category 2
Eye Irrit. 2: Se	rious eye damage/eye irritation – Category 2
	pecific target organ toxicity (single exposure) – Category 3
Data com	pared to the previous version altered.