

## Safety data sheet according to UK REACH

Printing date 02.08.2024

Version number 1.2

Revision: 02.08.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name: N20 FIBRE GLASS PUTTY**

· **Article number: N20**

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
use as industrial paint

· **Sector of Use**

SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Product category**

PC9a Coatings and paints, thinners, paint removers

PC9b Fillers, putties, plasters, modelling clay

· **Application of the substance / the mixture** refer to the relevant Technical Data Sheet

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

P.O. Box 7623

Beirut LEBANON

info@hymax.biz

Générale de Peinture, 70 Rue Cortambert 75116 Paris, France

Tel: +33(0)175293559

· **Further information obtainable from:** Product Safety Department

· **1.4 Emergency telephone number:** +33 (0)6 07 87 13 41

### SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008 with its amendment Regulation (EU) 2020/878**



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.

(Contd. on page 2)

## Safety data sheet according to UK REACH

Printing date 02.08.2024

Version number 1.2

Revision: 02.08.2024

**Trade name: N20 FIBRE GLASS PUTTY**

(Contd. of page 1)



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

#### Hazard pictograms



GHS02 GHS07 GHS08

#### Signal word Danger

#### Hazard-determining components of labelling:

styrene

#### Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

#### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### 2.3 Other hazards

#### Results of PBT and vPvB assessment

PBT: Not applicable.

(Contd. on page 3)

GB

## Safety data sheet according to UK REACH

Printing date 02.08.2024

Version number 1.2

Revision: 02.08.2024

**Trade name: N20 FIBRE GLASS PUTTY**

· **vPvB:** Not applicable.

(Contd. of page 2)

### SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 7727-43-7 EINECS: 231-784-4	barium sulphate, natural substance with a Community workplace exposure limit	>10-≤25%
CAS: 100-42-5 EINECS: 202-851-5 Reg.nr.: 01-2119457861-32	styrene ⚠ Flam. Liq. 3, H226; ⚠ Repr. 2, H361d; STOT RE 1, H372; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	>10-≤25%
CAS: 112945-52-5	silicon dioxide ⚠ Eye Irrit. 2, H319; STOT SE 3, H335	≤2.5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet

(Contd. on page 4)



## Safety data sheet according to UK REACH

Printing date 02.08.2024

Version number 1.2

Revision: 02.08.2024

**Trade name: N20 FIBRE GLASS PUTTY**

(Contd. of page 3)

- **5.2 Special hazards arising from the substance or mixture**  
*During heating or in case of fire poisonous gases are produced.*
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
*Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.*
- **6.2 Environmental precautions:** *Do not allow to enter sewers/ surface or ground water.*
- **6.3 Methods and material for containment and cleaning up:**  
*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.*
- **6.4 Reference to other sections**  
*See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.*

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
*Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.*
- **Information about fire - and explosion protection:**  
*Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.*
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** *No special requirements.*
- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:** *Keep container tightly sealed.*
- **Storage class:** 3
- **7.3 Specific end use(s)** *No further relevant information available.*

GB

(Contd. on page 5)

## Safety data sheet according to UK REACH

Printing date 02.08.2024

Version number 1.2

Revision: 02.08.2024

**Trade name: N20 FIBRE GLASS PUTTY**

(Contd. of page 4)

### SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see section 7.

- **Ingredients with limit values that require monitoring at the workplace:**

**7727-43-7 barium sulphate, natural**

WEL	Long-term value: 10* 4** mg/m <sup>3</sup> *inhalable dust **respirable dust
-----	---

**100-42-5 styrene**

WEL	Short-term value: 1080 mg/m <sup>3</sup> , 250 ppm Long-term value: 430 mg/m <sup>3</sup> , 100 ppm
-----	--

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes and skin.

- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

**Safety data sheet**  
according to UK REACH

Printing date 02.08.2024

Version number 1.2

Revision: 02.08.2024

**Trade name: N20 FIBRE GLASS PUTTY**

(Contd. of page 5)

· **Eye protection:**



Tightly sealed goggles

**SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

<b>Form:</b>	putty
<b>Colour:</b>	olive green
· <b>Odour:</b>	Characteristic
· <b>Odour threshold:</b>	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

<b>Melting point/freezing point:</b>	Undetermined.
<b>Initial boiling point and boiling range:</b>	145 °C

· **Flash point:** 31 °C

· **Flammability (solid, gas):** Flammable.

· **Auto-ignition temperature:** 480 °C

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

<b>Lower:</b>	1.2 Vol %
<b>Upper:</b>	8.9 Vol %

· **Vapour pressure at 20 °C:** 6 hPa

· <b>Density at 20 °C:</b>	1.49 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.

(Contd. on page 7)



## Safety data sheet according to UK REACH

Printing date 02.08.2024

Version number 1.2

Revision: 02.08.2024

**Trade name: N20 FIBRE GLASS PUTTY**

(Contd. of page 6)

· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b> <b>Dynamic:</b> <b>Kinematic:</b>	Not determined. Not determined.
· <b>Solvent content:</b> <b>Organic solvents:</b> <b>VOC (EC)</b>	14.5 % 216.5 g/l
<b>Solids content:</b>	83.3 %
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:****100-42-5 styrene**

Oral	LD50	5,000 mg/kg (rat)
Inhalative	LC50/4 h	24 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

(Contd. on page 8)

GB



## Safety data sheet according to UK REACH

Printing date 02.08.2024

Version number 1.2

Revision: 02.08.2024

**Trade name: N20 FIBRE GLASS PUTTY**

(Contd. of page 7)

- **Additional toxicological information:**
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**  
Suspected of damaging the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**  
Causes damage to the hearing organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

GB

(Contd. on page 9)



**Safety data sheet  
according to UK REACH**

Printing date 02.08.2024


Version number 1.2

Revision: 02.08.2024

**Trade name: N20 FIBRE GLASS PUTTY**

(Contd. of page 8)

**SECTION 14: Transport information**

<ul style="list-style-type: none"> <li>· <b>14.1 UN-Number</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>	<p align="right">UN1263</p>
<ul style="list-style-type: none"> <li>· <b>14.2 UN proper shipping name</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG, IATA</b></li> </ul>	<p align="right">1263 PAINT RELATED MATERIAL PAINT RELATED MATERIAL</p>
<ul style="list-style-type: none"> <li>· <b>14.3 Transport hazard class(es)</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>	<p align="right">NOT APPLICABLE</p>
<div style="text-align: center;">  </div> <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	<p align="right">3 Flammable liquids. 3</p>
<ul style="list-style-type: none"> <li>· <b>14.4 Packing group</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>	<p align="right">III</p>
<ul style="list-style-type: none"> <li>· <b>14.5 Environmental hazards:</b></li> <li>· <b>Marine pollutant:</b></li> </ul>	<p align="right">No</p>
<ul style="list-style-type: none"> <li>· <b>14.6 Special precautions for user</b></li> <li>· <b>EMS Number:</b></li> <li>· <b>Stowage Category</b></li> </ul>	<p align="right">Warning: Flammable liquids. F-E, S-E A</p>
<ul style="list-style-type: none"> <li>· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b></li> </ul>	<p align="right">Not applicable.</p>
<p>· <b>Transport/Additional information:</b></p>	
<ul style="list-style-type: none"> <li>· <b>ADR</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li> </ul>	<p align="right">5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p>
<ul style="list-style-type: none"> <li>· <b>IMDG</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li> </ul>	<p align="right">5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p>

(Contd. on page 10)



## Safety data sheet according to UK REACH

Printing date 02.08.2024

Version number 1.2

Revision: 02.08.2024

**Trade name: N20 FIBRE GLASS PUTTY**

(Contd. of page 9)

**UN "Model Regulation":** UN 1263 PAINT RELATED MATERIAL, 3, III

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Poisons Act**

- **Regulated explosives precursors**

None of the ingredients is listed.

- **Regulated poisons**

None of the ingredients is listed.

- **Reportable explosives precursors**

None of the ingredients is listed.

- **Reportable poisons**

None of the ingredients is listed.

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

- **Seveso category P5c** FLAMMABLE LIQUIDS

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

- **Department issuing SDS:** Product safety department

- **Contact:** N/A

(Contd. on page 11)

GB



## Safety data sheet according to UK REACH

Printing date 02.08.2024

Version number 1.2

Revision: 02.08.2024

**Trade name: N20 FIBRE GLASS PUTTY**

(Contd. of page 10)

**Abbreviations and acronyms:***ICAO: International Civil Aviation Organisation**RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)**ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**IATA: International Air Transport Association**GHS: Globally Harmonised System of Classification and Labelling of Chemicals**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**VOC: Volatile Organic Compounds (USA, EU)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**Flam. Liq. 3: Flammable liquids – Category 3**Acute Tox. 4: Acute toxicity – Category 4**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**Repr. 2: Reproductive toxicity – Category 2**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1***\* Data compared to the previous version altered.**