

N81Y– Smooth Polyester Putty Beige



Product Description

This great metal filler is a multi-purpose putty with an extremely smooth application. It can be applied vertically without running and exhibits high resistance to almost all solvents. It is characterized by very easy sanding and the advantage of withstanding temperatures of 100°C without any distortions.

Suitable Substrates:

- Iron, steel plate, glass fiber reinforced plastic
- Original paints or aged topcoat finishes

Surface Preparation:

- Clean well the surface to be treated with S241 GenClean. Make sure it is dry and free from
- Silicone, wax, grease and any extraneous material.

Product Application



1:0.03
3% Hymax Hardener



Application with Putty Knife



< 30 min at 20°C



4-5 minutes at 1m.

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.

N81Y – Smooth Polyester Putty Beige



Initial Sanding with P60 – P120 roughing-out
Final Sanding with P180 – P220 finishing

Product Characteristics

VOC(EC):

2004/42/IIIB (b) (250)250. The EU limit value for this product (product category IIB.b) in ready to use form is max 250g/ltr. The VOC content of this product in ready for use form is max. 250 g/l

Specific Gravity:

1.82 kg/cm³

Solids:

88.7%

SDS:

Refer to the Safety Data Sheet

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.