

Page 1/13


Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.05.2024

Version number 1.1

Revision: 30.05.2024



2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008) with its amendment Regulation (EU) 2020/878



3 H226 Flammable liquid and vapour.

(Contd. on page 2)



Page 2/13

Safety data sheet


according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.05.2024

Version number 1.1

Revision: 30.05.2024

Trade name: T360 2K MOLYBDATE ORANGE





Page 3/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.05.2024

Version number 1.1

Revision: 30.05.2024

Trade name: T360 2K MOLYBDATE ORANGE

	(Contd. of page 2)
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361-	+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/ international regulations.
· Additional i	information:
	ethyl methacrylate, 2,3-epoxypropyl neodecanoate, 2-hydroxyethyl methacrylate. May allergic reaction.
2.3 Other ha	azards

· Results of PBT and vPvB assessment

- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

123-86-4	n-butyl acetate	>10- <i>≤</i> 25%
	🔗 Flam. Liq. 3, H226; 🚯 STOT SE 3, H336	
1330-20-7		>2.5- <i>≤</i> 10%
	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
12656-85-8	Lead chromate molybdate sulfate red	>2.5- <i>≤</i> 10%
	Carc. 1B, H350; Repr. 1A, H360Df; STOT RE 2, H373; Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
108-65-6	2-methoxy-1-methylethyl acetate	>2.5- <i>≤</i> 10%
	🚸 Flam. Liq. 3, H226	
64742-95-6	Solvent naphtha (petroleum), light arom.	<i>≤</i> 2.5%
	🚸 Acute Tox. 4, H332; STOT SE 3, H335	
1309-64-4	antimony trioxide	<i>≤</i> 2.5%
	상 Carc. 2, H351	
80-62-6	methyl methacrylate	<i>≤</i> 2.5%
	♦ Flam. Liq. 2, H225; ♦ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
26761-45-5	2,3-epoxypropyl neodecanoate	<i>≤</i> 2.5%
	♦ Acute Tox. 3, H331; ♦ Aquatic Chronic 2, H411; ♦ Skin Irrit. 2, H315; Skin Sens. 1, H317	

LB/AR



according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.05.2024

Version number 1.1

Revision: 30.05.2024

(Contd. of page 3)

*≤*2.5%

Page 4/13

Trade name: T360 2K MOLYBDATE ORANGE

868-77-9 2-hydroxyethyl methacrylate

🚸 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317

· SVHC

12656-85-8 Lead chromate molybdate sulfate red

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 5)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.05.2024

Version number 1.1

Revision: 30.05.2024

(Contd. of page 4)

Page 5/13

Trade name: T360 2K MOLYBDATE ORANGE

Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

• **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Additional information about design of technical facilities: No further data; see section 7.

 Ingredients 	\cdot Ingredients with limit values that require monitoring at the workplace:	
	putyl acetate	
IOELV (EU)	Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm	
1330-20-7 xj	ylene	
IOELV (EU)	Short-term value: 442 mg/m³, 100 ppm Long-term value: 221 mg/m³, 50 ppm Skin	
	Lead chromate molybdate sulfate red	
BOELV (EU)	Long-term value: 0.005; 0.01*; 0.025** mg/m³ as Cr;*until 01/17/2025**processes generating fume	
	(Contd. on page 6)	



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.05.2024

Version number 1.1

Revision: 30.05.2024

Trade name: T360 2K MOLYBDATE ORANGE

(00.05.5.5	(Contd. of page 5)
	nethoxy-1-methylethyl acetate
IOELV (EU)	Short-term value: 550 mg/m ³ , 100 ppm
	Long-term value: 275 mg/m³, 50 ppm
	Skin
	hyl methacrylate
IOELV (EU)	Short-term value: 100 ppm
	Long-term value: 50 ppm
Additional i	nformation: The lists valid during the making were used as basis.
8.2 Exposur	e controls
Personal pro	otective equipment:
	tective and hygienic measures:
	rom foodstuffs, beverages and feed.
	remove all soiled and contaminated clothing
	before breaks and at the end of work.
	ive clothing separately.
Respiratory	
	rief exposure or low pollution use respiratory filter device. In case of intensive or longer e self-contained respiratory protective device.
Protection of	
(m)	
Pro	otective gloves
The alove m	aterial has to be impermeable and resistant to the product/ the substance/ the preparation.
	ing tests no recommendation to the glove material can be given for the product/ the
	the chemical mixture.
	the glove material on consideration of the penetration times, rates of diffusion and the
degradation	
Material of g	loves
	n of the suitable gloves does not only depend on the material, but also on further marks of
	varies from manufacturer to manufacturer. As the product is a preparation of several
	the resistance of the glove material can not be calculated in advance and has therefore to
	prior to the application.
	time of glove material
	eak through time has to be found out by the manufacturer of the protective gloves and has
to be observe	
	(Contd. on page 7)

Page 6/13



according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.05.2024

Version number 1.1

Revision: 30.05.2024

Trade name: T360 2K MOLYBDATE ORANGE

· Eye protection:

Tightly sealed goggles

SECTION 9: Physical and chemical properties

General Information Appearance:	
Form:	Liquid
Colour:	Orange
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	124 °C
Flash point:	25 °C
Flammability (solid, gas):	Flammable.
Auto-ignition temperature:	315 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
Vapour pressure at 20 °C:	10.7 hPa
Density at 20 °C:	1.102 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.

-....

Page 7/13

(Contd. of page 6)



Page 8/13

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.05.2024

Version number 1.1

Revision: 30.05.2024

Trade name: T360 2K MOLYBDATE ORANGE

	(Contd. of pa	age 7
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	42.0 %	
VÕC (EC)	462.9 g/l	
Solids content:	57.5 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

12656-85-8 Lead chromate molybdate sulfate red

Oral LD50 >5,000 mg/kg (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.

(Contd. on page 9)



Page 9/13

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.05.2024

Version number 1.1

Revision: 30.05.2024

(Contd. of page 8)

Trade name: T360 2K MOLYBDATE ORANGE

- Carcinogenicity May cause cancer.
- **Reproductive toxicity** May damage the unborn child. Suspected of damaging fertility.
- STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

(Contd. on page 10)

I B/AR



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.05.2024

Version number 1.1

Revision: 30.05.2024

Trade name: T360 2K MOLYBDATE ORANGE

(Contd. of page 9)

Page 10/13

14.1 UN-Number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR IMDG, IATA	1263 PAINT, ENVIRONMENTALLY HAZARDOUS PAINT
14.3 Transport hazard class(es)	NOT APPLICABLE
ADR, IMDG	
Class	3 Flammable liquids.
Label	3
Class	3 Flammable liquids. 3
Label	3
14.4 Packing group	3 III
 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: 	III No
 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: Marine pollutant: 	<i>III</i>
 Label 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: Marine pollutant: Special marking (ADR): 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category 	III No Symbol (fish and tree)



Page 11/13

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.05.2024

Version number 1.1

Revision: 30.05.2024

(Control of many a do)

Trade name: T360 2K MOLYBDATE ORANGE

· Transport/Additional information:	
ADR	
 Limited quantities (LQ) 	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 m
Transport category	3
 Tunnel restriction code 	D/E
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities (ÉQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 m
UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALL HAZARDOUS

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category
 E2 Hazardous to the Aquatic Environment
 P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- Additional classification according to Decree on Hazardous Materials, Annex II: Carcinogenic hazardous material group III (dangerous).
- Information about limitation of use: Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57
- 12656-85-8 Lead chromate molybdate sulfate red

(Contd. on page 12)

LB/AR



Page 12/13

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.05.2024

Version number 1.1

Revision: 30.05.2024

Trade name: T360 2K MOLYBDATE ORANGE

(Contd. of page 11)

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- Highly flammable liquid and vapour. H225
- H226 Flammable liquid and vapour.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H350 May cause cancer.
- H351 Suspected of causing cancer.
- H360Df May damage the unborn child. Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- · Department issuing SDS: Product safety department
- · Contact: N/A

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- SVHC: Substances of Very High Concern
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids Category 2
- Flam. Liq. 3: Flammable liquids Category 3
- Acute Tox. 4: Acute toxicity Category 4 Acute Tox. 3: Acute toxicity Category 3

(Contd. on page 13)

LB/AR



according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.05.2024

Version number 1.1

Revision: 30.05.2024

(Contd. of page 12)

Page 13/13

Trade name: T360 2K MOLYBDATE ORANGE

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Carc. 1B: Carcinogenicity – Category 1B Carc. 2: Carcinogenicity – Category 2 Repr. 1A: Reproductive toxicity – Category 1A STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 • * Data compared to the previous version altered.

LB/AR